

Safety Data Sheet according to Regulation (EC) No.1907/2006

<Annex II REACH>

1 Identification of the substance and the supplier

Product Identification **B-515 Mr. SURFACER 1200** **(AEROSOL)**
Product Code W1011GF027

Manufacturer's name : GSI Creos Corporation
Address : 3-1, Kudanminami 2-chome, Chiyoda-ku, Tokyo 102-0074, Japan
Business Group in Charge : Hobby Dept.
Phone and facsimile number for information : Tel; +81-03-5211-1805 Fax; +81-03-5211-1902
Emergency Contact : GSI Europe-Import + Export GmbH
 Louise-Dumont-Str. 31, 40211 Dusseldorf, Germany /Tel:49-211-166594-0

Classification of Product : Acrylic Coating
General Use : Coating for Plastics
Date prepared : 01/May/2015

2 Hazards identification

Classification of the substance or mixture
Classification (REGULATION (EC) No 1272/2008)

Flam. Aerosol Category 1	H222: Extremely flammable aerosol
Acute Toxicity Category 4	H302: Harmful if swallowed
Skin Irritation, Category 2	H315: Causes skin irritation
Eye Damage, Category 1	H318: Causes serious eye damage
Specific target organ toxicity - single exposure, Category 3	H335: May cause respiratory irritation
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness

Classification (67/548EEC, 1999/45/EC)

Highly Flammable	R12: Extremely flammable
Harmful	R22: Harmful if swallowed
Irritant	R37/38: Irritating to respiratory system and skin
Irritant	R41: Risk of serious damage to eyes
	R66: Repeated exposure may cause skin dryness or cracking
	R67: Vapours may cause drowsiness and dizziness

Labelling elements
Labelling (Regulation (EC) No 1272/2008)

Hazardous pictograms



Signal word Danger

Hazard Statements

H222: Extremely flammable aerosol
H229: Pressurized container: may burst if heated
H302: Harmful if swallowed
H315: Causes skin irritation
H318: Causes serious eye damage
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness
EUH066: Repeated exposure may cause skin dryness or cracking

Precautionary statements

Prevention
P102: Keep out of reach of children
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P280: Wear protective gloves/protective clothing/eye protection/face protection

Reaction:
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses if present and easy to do. continue rinsing.

Hazardous components which must be listed on the label:

CAS 71-36-3 Butan-1-ol

Other hazards ---

Further information ---

3 Composition/Information on Ingredients

Mixtures

Mixture of solvents in aerosol can

Chemical Name	CAS-No.	EC No.	Registration Number	Classification (67/548/EEC)	Classification (REGULATION (EC) No. 1272/2008)	Conc.(wt%)
n-Butyl-acetate	123-86-4	204-658-1	01-2119485493-29-XXXX	R10 R67 R66	Flam. Liq. 3; H226 STOT SE 3; H336	1-5
1-Methoxy-2-propanol	107-98-2	203-539-1	01-2119457435-35-XXXX	R10 R67	Flam. Liq. 3; H226 STOT SE 3; H336	1-5
Ethanol	64-17-5	200-578-6	01-2119457610-43-XXXX	F; R11	Flam. Liq. 2; H225	1-5
Butanone	78-93-3	201-159-0	01-2119457290-43-XXXX	F; R11 Xi; R36 R67 R66	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	1-5
Butan-1-ol	71-36-3	200-751-6	01-2119484630-38-XXXX	R10 Xn; R22 Xi; R37/38 R41 R67	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 STOT SE 3; H336	5-10
4-Hydroxy-4-methylpentan-2-one	123-42-2	204-626-7	01-2119473975-21-XXXX	Xi; R36	Eye Irrit. 2; H319	5-10
Dimethyl ether	115-10-6	204-065-8	01-2119472128-37-XXXX	F+; R12	Press.Gas Flam. Gas 1; H220	40-50

For the full text of the R-phrases mentioned in this section, see section 16.

For the full text of the H-statements mentioned in this section, see section 16.

4 First-Aid measures

[If in Eyes]

- Wash eyes with plenty of water and in case of persistence of irritation, get medical attention.

[If on Skin]

- Wash with plenty of soap and water, and get medical attention immediately.

[If Inhaled]

- If feel unwell because of inhalation, remove to fresh air and keep at rest in a position comfortable for breathing, and call a physician.

[If Swallowed]

- Call a physician immediately.

5 Fire-Fighting measures

Suitable extinguishing media: Water[] CO2[*] Foam[*] Dry chemical[*] Dry sand[*]

Fire fighting method

- Wear proper protective clothes such as heat insulating clothes/gloves/face shield and/or eye protection.

- Use specified extinguishing media.
- Remove combustible material from surrounding area.
- Start fire fighting from windward
- Do not use water as the extinguishing media.

6 Accidental release measures

- Avoid contact with skin. Wear appropriate protective equipment (protective gloves, eye/face protection, apron and long sleeved clothes) when handling spill of this product.
- Wear protective equipment and collect spillage into air-tight container that can be tightly closed. Move the container to a safe place.
- Dispose contaminant and waste in accordance with regulations relative to disposal.
- Eliminate all ignition sources such as heat, sparks, open flames and combustible materials.
- Provide appropriate extinguisher to prepare for fire.
- Do not use steel tools as it may cause impact sparks. Tool should be static free.
- Absorb with dry sand, earth or noncombustible material. In case of large spill, hold back with earth to prevent spreading.
- Avoid release to rivers to prevent effect to environment.

7 Handling and storage

[Cautions on Handling]

- May cause poisoning if on skin or inhaled.
- Keep away from ignition sources such as heat/sparks/open flame, and ventilate work area when handling this product.
- Ventilate work area to prevent inhalation of vapor/fume/spray/dust.
- Avoid contact with skin. Wear protective gloves, eye/face protection and long sleeved clothes if necessary.
- If spilled or leaked, wipe with cloth and discard contaminated materials into a container which is filled with water.
- Dip contaminated cloth, spray dust and/or mist into water until they are discarded properly.
- After use, wash hands and gargle mouth thoroughly.
- Do not use this product other than the purpose specified by the manufacturer/supplier.

[Cautions on Storage]

- Keep container tightly closed. Store in cool and ventilated indoor place. Protect from direct sun light.
- Keep reach out of children.
- Keep away from flame or heat sources.

8 Exposure Controls/Personal Protection

[Facilities Recommendation]

- All facilities should be explosion proof.
- Prevent vapor from retention by installation of a proper ventilator.
- Ground/bond container or receiving equipment for transportation, mixing and/or transferring of this product.
- Do not locate heat/flame generating facilities close to the work area.
- If spray indoor, install coating facilities so that workers are protected from direct exposure to spray mist, or install adequate ventilation.
- For handling in closed tanks, install appropriate ventilator which secures ventilation to the bottom of the tank.

[Protective Equipments]

- Respiratory Protection: Wear gas mask for organic gas. Wear self-contained breathing apparatus in case of operation in closed areas.
- Eye Protection: Wear goggle type of eye protection.
- Skin Protection: Wear appropriate gloves which is impervious to organic solvents and chemicals.
- Other Protection: Work clothes specified by the manufacturer or supplier, and safety shoes.

Substance	CAS No.	Exposure Limit Value			
		Short Term		Eight Hours	
		EU	AGS&DFG Germany	EU	AGS&DFG Germany
n-Butyl acetate	123-86-4		200PPM		100PPM
1-Methoxypropan-2-ol	107-98-2	150PPM	200PPM	100PPM	100PPM
Ethanol	64-17-5		1000PPM		500PPM
Butan-2-one	78-93-3	300PPM	200PPM	200PPM	200PPM
Butan-1-ol	71-36-3		100PPM		100PPM
4-Hydroxy-4-methylpentan-2-one	123-42-2		40PPM		20PPM
Dimethyl ether	115-10-6		8000PPM	1000PPM	1000PPM

9 Physical and Chemical Properties

Physical appearance

Color: Colorless/Clear

Form: Aerosol/Liquid

Odor: Product-specific

Additional data

Change of state: Pressure of gas is immediately ejected gas. Sprayed solvents evaporate quickly.
Boiling point/ range: N.A.(Not applicable)
Flash point: N.A.
Flammability: Spray and evaporative gases are extremely flammable
Ignition temperature: N.A.
Auto ignition: No
Oxidizing properties: The case of overheating
Explosion danger: Overheating rupture/bursting of the container formation of explosive mixtures are possible.
Explosion limits: N.A.
Vapour pressure inside the dispenser: at 50°C maximum 2/3 of maximum pressure allowed for the dispenser
Density, here: apparent density at 20°C: 0.850g/cm3
Solubility in water: Yes
Solvent content: 30-50%
More details: The finished preparation in the aerosol dispenser only upon the addition of the pressurized gas. Details are in the hermetically sealed under pressure not measurable container.

10 Stability and Reactivity

[Reactivity Information]

- Materials to be avoided: Keep away from strong oxides and/or peroxides that will cause polymerization and/or generate heat or fire by mixing or contact.
- Hazardous thermal decomposition products: CO, CO₂, HCl, vapors of solvents.
- Other reactivity information: None.

11 Toxicological Information

Health Hazard Information on Ingredient Table 1

Substance name	Acute toxicity (LD50, LC50, etc.)				
	Oral	Dermal	Inhalation (Gas)	Inhalation (Vapor)	Inhalation (Dust, Mist)
Ethanol	Not Categorized > 5000mg/kg	Not Classifiable	Not Applicable	Not Categorized	Not Categorized
2-Butanone	Category 5 2483mg/kg	Not Categorized	Not Applicable	Category 5 11700ppm	Not Classifiable
1-Butanol	Category 4 1227mg/kg	Category 5 3636mg/kg	Not Applicable	Not Categorized	Not Classifiable
2-Pentanone, 4-hydroxy-4-methyl-	Category 5 4000mg/kg	Not Categorized	Not Applicable	Not Classifiable	Not Classifiable
2-Pentanone, 4-methyl-	Category 5 2919mg/kg	Category 5 3000mg/kg	Not Applicable	Category 3 2000ppm	Not Classifiable
Acetic acid, butyl ester	Not Categorized 14130mg/kg	Not Categorized	Not Applicable	Category 3 2000ppm	Category 4 1.85mg/l
2-Propanol, 1-methoxy-	Not Categorized 5113mg/kg	Not Categorized	Not Applicable	Not Classifiable	Not Classifiable
Silicon dioxide	Category 5 3160mg/kg	Not Classifiable	Not Applicable	Not Classifiable	Not Classifiable
Titanium oxide (TiO ₂)	Not Categorized > 10000mg/kg	Not Categorized	Not Applicable	Not Classifiable	Not Categorized

Health Hazard Information on Ingredient Table 2

Substance name	Skin Corrosion - Irritation	Serious Damage to Eyes, Eye Irritation	Respiratory Sensitization	Skin Sensitization	Germ Cell Mutagenicity	Carcinogenicity
Ethanol	Not Categorized	Category 2A-2B	Not Classifiable	Not Classifiable	Category 1B	Not Categorized
2-Butanone	Category 2	Category 2B	Not Classifiable	Not Classifiable	Not Categorized	Not Categorized
1-Butanol	Category 2	Category 2A	Not Classifiable	Not Classifiable	Not Categorized	Not Categorized
2-Pentanone, 4-hydroxy-4-methyl-	Category 2	Category 2A	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable
2-Pentanone, 4-methyl-	Not Categorized	Not Categorized	Not Classifiable	Not Categorized	Not Categorized	Not Categorized
Acetic acid, butyl ester	Category 3	Category 2B	Not Categorized	Not Classifiable	Not Classifiable	Not Classifiable
2-Propanol, 1-methoxy-	Category 3	Category 2A-2B	Not Classifiable	Not Classifiable	Not Categorized	Not Classifiable
Silicon dioxide	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Categorized
Titanium oxide (TiO ₂)	Not Categorized	Category 2B	Not Classifiable	Not Categorized	Not Categorized	Not Categorized

Health Hazard Information on Ingredient Table 3

Substance name	Reproductive toxicity	Specific Target Organ (Single Exposure)
Ethanol	Category 1A	Category 3(Respiratory tract irritation, Narcotic action)
2-Butanone	Not Categorized	Category 1(Central nervous system) Category 2(Kidney) Category 3(Respiratory tract irritation)
1-Butanol	Not Categorized	Category 3(Respiratory tract irritation, Narcotic action)
2-Pentanone, 4-hydroxy-4-methyl-	Category 2	Category 1(Respiratory system) Category 2(Liver) Category 3(Narcotic action)
2-Pentanone, 4-methyl-	Not Categorized	Category 3(Respiratory tract irritation, Narcotic action)
Acetic acid, butyl ester	Not Categorized	Category 1(Central nervous system) Category 2(Lung) Category 3(Respiratory tract irritation)

2-Propanol, 1-methoxy-	Not Categorized	Category 3(Narcotic action)
Silicon dioxide	Not Classifiable	Not Classifiable
Titanium oxide (TiO2)	Not Classifiable	Category 3(Respiratory tract irritation)

Health Hazard Information of Ingredient Table 4

Substance name	Specific Target Organ (Repeat Exposure)	Aspiration Respiratory Toxicity
Ethanol	Category 1(Liver) Category 2(Nerve)	Not Classifiable
2-Butanone	Category 1(Central nervous system, Peripheral nervous system)	Category 2
1-Butanol	Category 1(Central nervous system, Auditory organ)	Category 2
2-Pentanone, 4-hydroxy-4-methyl-	Category 1(Kidney)	Not Classifiable
2-Pentanone, 4-methyl-	Category 1(Systemic toxicology)	Category 2
Acetic acid, butyl ester	Not Classifiable	Not Classifiable
2-Propanol, 1-methoxy-	Not Categorized	Not Classifiable
Silicon dioxide	Not Classifiable	Not Classifiable
Titanium oxide (TiO2)	Not Classifiable	Not Classifiable

12 Ecological information

Aqueous Milieu Hazard Information on Ingredient

Substance name	Hazardous to Aquatic Environment (Acute)	Hazardous to Aquatic Environment (Chronic)
Ethanol	Not Categorized	Not Categorized
2-Butanone	Not Categorized	Not Categorized
1-Butanol	Not Categorized	Not Categorized
2-Pentanone, 4-hydroxy-4-methyl-	Not Categorized	Not Categorized
2-Pentanone, 4-methyl-	Not Categorized	Not Categorized
Acetic acid, butyl ester	Category 3	Not Categorized
2-Propanol, 1-methoxy-	Not Categorized	Not Categorized
Silicon dioxide	Not Classifiable	Not Classifiable
Titanium oxide (TiO2)	Not Categorized	Category 4

13 Disposal Considerations

- Content should be used up before disposal of container.
- Container/content should be disposed in accordance with local, regional and national regulations.

14 Transport Information

14.1 UN number

ADR : 1950
IMDG : 1950
IATA : 1950

14.2 Proper shipping name

ADR : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class

ADR : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADR :
Classification Code : 5F
Tunnel restriction code : (D)
IMDG :
EmS Number : F-D, S-U
IATA :
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203

14.5 Environmental hazards

ADR :
Environmentally hazardous : yes
IMDG :

Marine pollutant : no
IATA
Environmentally hazardous : no

14.6 Special precautions for user
For personal protection see section 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No data available

15 Regulatory Information

Particular hazards associated with the preparation and safety recommendations:

16 Other Information

Full text risk of R-phrases referred to under sections 2 and 3:

R10: Flammable
R11: Highly flammable
R12: Extremely flammable
R22: Harmful if swallowed
R36: Irritating to eyes
R37/38: Irritating to respiratory system and skin
R41: Risk of serious damage to eyes
R66: Repeated exposure may cause skin dryness or cracking
R67: Vapours may cause drowsiness and dizziness

Full text risk of H-statements referred to under sections 2 and 3:

H220: Extremely flammable gas
H222: Extremely flammable aerosol
H225: Highly flammable liquid and vapour
H226: Flammable liquid and vapour
H229: Pressurized container: may burst if heated
H302: Harmful if swallowed
H315: Causes skin irritation
H318: Causes serious eye damage
H319: Causes serious eye irritation
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness
EUH066: Repeated exposure may cause skin dryness or cracking

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Parts of the Safety Data Sheet marked with red line are updated.