Safety Data Sheet according to Regulation (EC) No.1907/2006 <Annex II REACH>

1 Identification of the substance and the supplier

B-524 Mr.PRIMER SURFACER 1000 Product Identification

Product Code W1011GF034

Manufacturer's name : GSI Creos Corporation

Address : 3-1, Kudanminami 2-chome, Chiyoda-ku, Tokyo 102-0074, Japan

: HOBBY DEPT. Business Group in Charge

Phone and facsimile number for information : Tel; +81-03-5211-1805 Fax; +81-03-5211-1902

Emergency Contact : GSI Europe-Import + Export GmbH

Louise-Dumont-Str. 31, 40211 Dusseldorf, Germany /Tel:49-211-166594-0

Classification of Product : Acrylic Coating General Use : Coating for Plastics Date prepared : 01/May/2015

2 Hazards identification

Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flam. Aerosol Cathegory 1 H222: Extremely flammable aerosol Acute Toxity Cathegory 4 H302: Harmful if swallowed Skin Irritation, Cathegory 2 H315: Causes skin irritation Eye Damage, Cathegory 1 H318: Causes serious eye damage Acute Toxity Cathegory 4 H332: Harmful if inhaled

Specific target organ toxicity - single

exposure, Cathegory 3

Specific target organ toxicity - single

exposure, Cathegory 3

H336: May cause drowsiness or dizziness

H335: May cause respiratory irritation

Classification (67/548EEC, 1999/45/EC)

Highly Flammable R12: Extremely flammable

Harmful R20/22: Harmful by inhalation and if swallowed Irritant R37/38: Irritating to respiratory system and skin

Irritant R41: Risk of serious damage to eyes

R66: Repeated exposure may cause skin dryness or cracking

R67: Vapours may cause drowsiness and dizziness

Labelling elements

Labelling (Regulation (EC) No 1272/2008)

Hazardous pictograms



Signal word Danger

Hazard Statements H222: Extremely flammable aerosol

H229: Pressurized container: may burst if heated

H302: Harmful if swallowed H315: Causes skin irritation H318: Causes serious eye damage H332: Harmful if inhaled H335: May cause respiratory irritation

H336: May cause drowsiness or dizziness

EUH066: Repeated exposure may cause skin dryness or cracking

Precautionary statements

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection

Reaction:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do. continue rinsing.

Hazardous components which must be listed on the label:

CAS 108-10-1 4-Methylpentan-2-one

CAS 71-36-3 Butan-1-ol CAS 108-94-1 Cyclohexanone

Other hazards ---

Further information ---

3 Composition/Information on Ingredients Mixtures

Mixture of solvents in aerosol can

Chemical Name	CAS-No.	EC No.	Registration Number		Classification (REGULA- TION (EC) No. 1272/2008	Conc.(wt%)
Propan-2-ol	67-63-0	200-661-7	01- 2119457558- 25-XXXX	F; R11	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	1-5
n-Butyl-actetate	123-86-4	204-658-1	01- 2119485493- 29-XXXX	R10	Flam. Liq. 3; H226 STOT SE 3; H336	5-10
2-Methoxy-1-methylethyl acetate	108-65-6	203-603-9	01- 2119475791- 29-XXXX	R10	Flam. Liq. 3; H226	1-5
Ethyl acetate	141-78-6	205-500-4	01- 2119475103- 46-XXXX	F; R11 Xi; R36 R67 R66	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H335	1-5
Cyclohexanone	108-94-1	203-631-1	01- 2119453616- 35-XXXX	R10	Flam. Liq. 3; H226 Acute Tox. 4; H332	1-5
Ethanol	64-17-5	200-578-6	01- 2119457610- 43-XXXX	F; R11	Flam. Liq. 2; H225	1-5
Butanone	78-93-3	201-159-0	01- 2119457290- 43-XXXX	F; R11 Xi; R36 R67 R66	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	1-5
Butan-1-ol	71-36-3	200-751-6	01- 2119484630- 38-XXXX	R10 Xn; R22 Xi; R37/38 R41 R67	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 STOT SE 3: H336	1-5
4-Hydroxy-4-methylpentan- 2-one	123-42-2	204-626-7	01- 2119473975- 21-XXXX	Xi; R36	Eye Irrit. 2; H319	5-10
4-Methylpentan-2-one	108-10-1	203-550-1	01- 2119473980- 30-XXXX	F; R11 Xn; R20 Xi; R36/37 R66	Flam. Liq. 2; H225 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335	1-5
Dimethyl ether	115-10-6	204-065-8	01- 2119472128- 37-XXXX	F+; R12	Press.Gas Flam. Gas 1; H220	50-60

For the full text of the R-phrases mentioned in this section, see section 16. For the full text of the H-statements mentioned in this section, see section 16.

4 First-Aid measures

[If in Eyes]

[·] Wash eyes with plenty of water and in case of persistence of irritation, get medical attention.

[If on Skin]

· Wash with plenty of soap and water, and get medical attention immediately.

[If Inhaled]

- If feel unwell because of inhalation, remove to fresh air and keep at rest in a position comfortable for breathing, and call a physician. [If Swallowed]
- · Call a physician immediately.

5 Fire-Fighting measures

Suitable extinguishing media Water[] CO2[*] Foam[*] Dry chemical[*] Dry sand[*]

Fire fighting method

- · Wear proper protective clothes such as heat insulating clothes/gloves/face shield and/or eye protection.
- · Use specified extinguishing media.
- · Remove combustible material from surrounding area.
- · Start fire fighting from windward
- Do not use water as the extinguishing media.

6 Accidental release measures

- · Avoid contact with skin. Wear appropriate protective equipment (protective gloves, eye/face protection, apron and long sleeved clothes) when handling spill of this product.
- · Wear protective equipment and collect spillage into air-tight container that can be tightly closed. Move the container to a safe place.
- Dispose contaminant and waste in accordance with regulations relative to disposal.
- · Eliminate all ignition sources such as heat, sparks, open flames and combustible materials.
- Provide appropriate extinguisher to prepare for fire.
- Do not use steel tools as it may cause impact sparks. Tool should be static free.
- · Absorb with dry sand, earth or noncombustible material. In case of large spill, hold back with earth to prevent spreading.
- · Avoid release to rivers to prevent effect to environment.

7 Handling and storage

[Cautions on Handling]

- · May cause poisoning if on skin or inhaled.
- · Keep away from ignition sources such as heat/sparks/open flame, and ventilate work area when handling this product.
- · Ventilate work area to prevent inhalation of vapor/fume/spray/dust.
- · Avoid contact with skin. Wear protective gloves eye/face protection and long sleeved clothes if necessary.
- If spilled or leaked, wipe with cloth and discard contaminated materials into a container which is filled with water.
- Dip contaminated cloth, spray dust and/or mist into water until they are discarded properly.
- After use, wash hands and gargle mouth thoroughly.
- Do not use this product other than the purpose specified by the manufacturer/supplier.

[Cautions on Storage]

- · Keep container tightly closed. Store in cool and ventilated indoor place. Protect from direct sun light.
- · Keep reach out of children.
- Keep away from flame or heat sources.

8 Exposure Controls/Personal Protection

[Facilities Recommendation]

- All facilities should be explosion proof.
- Prevent vapor from retention by installation of a proper ventilator.
- Ground/bond container or receiving equipment for transportation, mixing and/or transferring of this product.
- Do not locate heat/flame generating facilities close to the work area.
- If spray indoor, install coating facilities so that workers are protected from direct exposure to spray mist, or install adequate ventilation.
- For handling in closed tanks, install appropriate ventilator which secures ventilation to the bottom of the tank.

[Protective Equipments]

- Respiratory Protection: Wear gas mask for organic gas. Wear self-contained breathing apparatus in case of operation in closed areas.
- · Eye Protection: Wear goggle type of eye protection.
- · Skin Protection: Wear appropriate gloves which is impervious to organic solvents and chemicals.
- Other Protection: Work clothes specified by the manufacturer or supplier, and safety shoes.

		Exposure Limit Value			
		Short Term		Eight	Hours
			AGS&DFG		AGS&DFG
Substance	CAS No.	EU	Germany	EU	Germany
Propan-2-ol	67-63-0		400PPM		200PPM
n-Butyl acetate	123-86-4		200PPM		100PPM
1-Methoxypropyl acetate (all isomers)	108-65-6	100PPM	50PPM	50PPM	50PPM
Ethyl acetate	141-78-6		800PPM		400PPM
cyclohexanone	108-94-1				

C.I. Pigment Green 7 1328-53-6

Butan-2-one 78-93-3 300PPM 200PPM 200PPM 200PPM Butan-1-ol 100PPM 100PPM 71-36-3 40PPM 20PPM 4-Hydroxy-4-methylpentan-2-one 123-42-2

9 Physical and Chemical Properties

Physical appearance

Colour Gray Form Aerosol/liquid Order Solvent odor

Additional data

Change of state Pressure of gas is immediately ejected gas.

Sprayed solvents evaporate quickly.

Boiling point/range Flash point Flammability -31°C

Spray and evaporative gases are extremely flammable.

Ignition temperature n.a. Auto Iginition no

Oxidizing properties the case of overheating

Explosion Danger overheating rupture/bursting of the container Formation of exposive mixtures are possible. n.a.* Explosion limits

at 50°C maximum 2/3 of maximum pressure Vapour pressure inside the dispenser

allowed for the dispenser Density, here: apparent density at 20°C 0.7~0.9g/cm3

Solubility in water yes Solvent content 30-50%

More details * The finished preparation in the aerosol dispenser only upon the addition of the pressurized gas.

* Details are in the hermetically sealed under

pressure not measurable container.

10 Stability and Reactivity

[Reactivity Information]

- Materials to be avoided: Keep away from strong oxides and/or peroxides that will cause polymerization and/or generate heat or fire by mixing or contact.
- · Hazardous thermal decomposition products: CO, CO2, HCl, vapors of solvents.
- · Other reactivity information: None.

11 Toxicological Information

Health Hazard Information on Ingredient Table 1

Substance name		Acute toxicity (LD50, LC50, etc.)					
Substance name	Oral	Dermal	Inhalation (Gas)	Inhalation (Vapor)	Inhalation (Dust, Mist)		
2-Propanol	Category 5	Category 5	Not Applicable	Not Categorized	Not Classifiable		
2-F Topanoi	3437mg/kg	4059mg/kg					
Cellulose, nitrate	Not Categorized	Not Classifiable	Not Applicable	Not Classifiable	Not Classifiable		
Cellulose, filtrate	> 5000mg/kg						
Acetic acid, butyl ester	Not Categorized	Not Categorized	Not Applicable	Category 3	Category 4		
Acetic acia, batyl estel	14130mg/kg			2000ppm	1.85mg/l		
Titanium oxide (TiO2)	Not Categorized	Not Categorized	Not Applicable	Not Classifiable	Not Categorized		
Titaliani oxide (1102)	> 10000mg/kg						
2-Propanol, 1-methoxy-, acetate	Not Categorized	Not Categorized	Not Applicable	Not Classifiable	Not Classifiable		
2-F Topanoi, 1-methoxy-, acetate	8532mg/kg	> 5000mg/kg					
Acetic acid ethyl ester	Not Categorized	Not Categorized	Not Applicable	Not Categorized	Not Classifiable		
Acetic acid etilyi estel	> 5000mg/kg						
Cyclohexanone	Category 4	Category 3	Not Applicable	Category 3	Not Categorized		
Cyclonexanone	1544mg/kg	947mg/kg		2450ppm			
Ethanol	Not Categorized	Not Classifiable	Not Applicable	Not Categorized	Not Categorized		
Ethanor	> 5000mg/kg						
2-Butanone	Category 5	Not Categorized	Not Applicable	Category 5	Not Classifiable		
	2483mg/kg			11700ppm			
1-Butanol	Category 4	Category 5	Not Applicable	Not Categorized	Not Classifiable		
1-Butarioi	1227mg/kg	3636mg/kg					
2-Pentanone 4-hydroxy-4-methyl-	Category 5	Not Categorized	Not Applicable	Not Classifiable	Not Classifiable		

[2-1 GITATIONS, T-HYDROXY-T-METHYF				1	
, , , , , , , , , , , , , , , , , , ,	4000mg/kg				
2-Pentanone, 4-methyl-	Category 5	Category 5	Not Applicable	Category 3	Not Classifiable
2-1 entanone, 4-metryi-	2919mg/kg	3000mg/kg		2000ppm	
Methane, oxybis-	Not Classifiable	Not Classifiable	Not Categorized	Not Applicable	Not Applicable
IVICTIANC, ONYDIS-					

Health Hazard Information on Ingredient Table 2

Substance name	Skin Corrosion • Irritation	Serious Damage to Eyes /Eye Irritation	Respiratory Sensitization	Skin Sensitization	Germ Cell Mutagenicity	Carcinogenicity
2-Propanol	Not Categorized	Category 2A-2B	Not Classifiable	Not Classifiable	Not Categorized	Not Categorized
Cellulose, nitrate	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable
Acetic acid, butyl ester	Category 3	Category 2B	Not Categorized	Not Classifiable	Not Classifiable	Not Classifiable
Titanium oxide (TiO2)	Not Categorized	Category 2B	Not Classifiable	Not Categorized	Not Categorized	Not Categorized
2-Propanol, 1-methoxy-, acetate	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable
Acetic acid ethyl ester	Not Categorized	Category 2B	Not Classifiable	Not Classifiable	Not Categorized	Not Classifiable
Cyclohexanone	Category 2	Category 2A	Not Classifiable	Not Categorized	Category 2	Category 2
Ethanol	Not Categorized	Category 2A-2B	Not Classifiable	Not Classifiable	Category 1B	Not Categorized
2-Butanone	Category 2	Category 2B	Not Classifiable	Not Classifiable	Not Categorized	Not Categorized
1-Butanol	Category 2	Category 2A	Not Classifiable	Not Classifiable	Not Categorized	Not Categorized
2-Pentanone, 4-hydroxy-4-methyl-	Category 2	Category 2A	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable
2-Pentanone, 4-methyl-	Not Categorized	Not Categorized	Not Classifiable	Not Categorized	Not Categorized	Not Categorized
Methane, oxybis-	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable

Health Hazard Information on Ingredient Table 3

Health Hazard Information on Ingredient Trable 3		
Substance name	Reproductive toxicity	Specific Target Organ (Single Exposure)
2-Propanol	Category 2	Category 1(Central nervous system, Kidney, Systemic toxicology) Category 3(Respiratory tract irritation)
Cellulose, nitrate	Not Classifiable	Category 3(Respiratory tract irritation)
Acetic acid, butyl ester	Not Categorized	Category 1(Central nervous system) Category 2(Lung) Category 3(Respiratory tract irritation)
Titanium oxide (TiO2)	Not Classifiable	Category 3(Respiratory tract irritation)
2-Propanol, 1-methoxy-, acetate	Not Classifiable	Not Classifiable
Acetic acid ethyl ester	Not Classifiable	Category 1(Respiratory system) Category 3(Narcotic effects)
Cyclohexanone	Category 2	Category 1(Liver, Spleen, Central nervous system) Category 2(Lung) Category 3(Narcotic effects, Respiratory tract irritation)
Ethanol	Category 1A	Category 3(Respiratory tract irritation, Narcotic effects)
2-Butanone	Not Categorized	Category 1(Central nervous system) Category 2(Kidney) Category 3(Respiratory tract irritation)
1-Butanol	Not Categorized	Category 3(Respiratory tract irritation, Narcotic effects)
2-Pentanone, 4-hydroxy-4-methyl-	Category 2	Category 1(Respiratory system) Category 2(Liver) Category 3(Narcotic effects)
2-Pentanone, 4-methyl-	Not Categorized	Category 3(Respiratory tract irritation, Narcotic effects)
Methane, oxybis-	Not Classifiable	(Narcotic effects)

Health Hazard Information of Ingredient Table 4

Health Hazard Information of Ingredient Table 4		
Substance name	Specific Target Organ (Repeat Exposure)	Aspiration Respiratory Toxicity
2-Propanol	Category 2(Blood vessel, Liver, Spleen)	Category 2
Cellulose, nitrate	Not Classifiable	Not Classifiable
Acetic acid, butyl ester	Not Classifiable	Not Classifiable
Titanium oxide (TiO2)	Not Classifiable	Not Classifiable
2-Propanol, 1-methoxy-, acetate	Not Classifiable	Not Classifiable
Acetic acid ethyl ester	Not Classifiable	Not Classifiable
Cyclohexanone	Category 1(Kidney, Liver, Central nervous system)	Category 2
Ethanol	Category 1(Liver) Category 2(Nerve)	Not Classifiable
2-Butanone	Category 1(Central nervous system, Peripheral nervous system)	Category 2
1-Butanol	Category 1(Central nervous system, Auditory organ)	Category 2
2-Pentanone, 4-hydroxy-4-methyl-	Category 1(Kidney)	Not Classifiable
2-Pentanone, 4-methyl-	Category 1(Systemic toxicology)	Category 2
Methane, oxybis-	Not Classifiable	Not Classifiable

12 Ecological information

Aqueous Milieu Hazard Information on Ingredient

Substance name	Hazardous to Aquatic Environment (Acute)	Hazardous to Aquatic Environment (Chronic)
2-Propanol	Not Categorized	Not Categorized
Cellulose, nitrate	Not Categorized	Not Categorized
Acetic acid, butyl ester	Category 3	Not Categorized
Titanium oxide (TiO2)	Not Categorized	Category 4
2-Propanol, 1-methoxy-, acetate	Not Classifiable	Not Classifiable
Acetic acid ethyl ester	Not Categorized	Not Categorized
Cyclohexanone	Not Categorized	Not Categorized
Ethanol	Not Categorized	Not Categorized
2-Butanone	Not Categorized	Not Categorized
1-Butanol	Not Categorized	Not Categorized
2-Pentanone, 4-hydroxy-4-methyl-	Not Categorized	Not Categorized
2-Pentanone, 4-methyl-	Not Categorized	Not Categorized
Methane, oxybis-	Not Categorized	Not Categorized

13 Disposal Considerations

- Content should be used up before disposal of container.
- Container/content should be disposed in accordance with local, regional and national regulations.

14 Transport Information

14.1 UN number

ADR : 1950 IMDG : 1950 IATA : 1950

14.2 Proper shipping name

ADR : AEROSOLS IMDG : AEROSOLS IATA : Aerosols, flammable

14.3 Transport hazard class

ADR : 2 IMDG : 2.1 IATA : 2.1

14.4 Packing group

ADR

Classification Code : 5F Tunnel restriction code : (D) IMDG

EmS Number : F-D, S-U

IATA

Packing instruction (cargo aircraft) : 203 Packing instruction (LQ) : Y203

14.5 Environmental hazards

ADR

Environmentally hazardous : yes IMDG

Marine pollutant : no IATA

Environmentally hazardous : no

14.6 Special precautions for user For personal protection see section 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

15 Regulatory Information

Particular hazards associated with the preparation and safety recommendations:

16 Other Information

Full text risk of R-phrases referred to under sections 2 and 3:

R10: Flammable

R11: Highly flammable R12: Extremely flammable R20: Harmful by inhalation

R20/22: Harmful by inhalation and if swallowed

R22: Harmful if swallowed R36: Irritating to eyes

R36/37: Irritating to eyes and respiratory system R37/38: Irritating to respiratory system and skin

R41: Risk of serious damage to eyes

R66: Repeated exposure may cause skin dryness or cracking

R67: Vapours may cause drowsiness and dizziness

Full text risk of H-statements referred to under sections 2 and 3:

H220: Extremely flammable gas

H222: Extremely flammable aerosol

H225: Highly flammable liquid and vapour

H226: Flammable liquid and vapour

H229: Pressurized container: may burst if heated

H302: Harmful if swallowed

H315: Causes skin irritation

H318: Causes serious eye damage

H319: Causes serious eye irritation

H332: Harmful if inhaled

H335: May cause respiratory irritation

H336: May cause drowsiness or dizziness

EUH066: Repeated exposure may cause skin dryness or cracking

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Parts of the Safety Data Sheet marked with red line are updated.