Safety Data Sheet according to Regulation (EC) No.1907/2006 <Annex II REACH>

1 Identification of the substance and the supplier

Product Identification B-529 Mr. FINISHING SURFACER 1500 WHITE

Product Code W1011GF041

Manufacturer's name : GSI Creos Corporation

Address : 3-1,Kudanminami 2-chome,Chiyoda-ku,Tokyo 102-0074,Japan

Business Group in Charge : HOBBY DEPT.

Phone and facsimile number for information : Tel;+81-03-5211-1805 Fax;+81-03-5211-1902

Emergency Contact : Tel;49-211-166594-0 / GSI Europe-Import+Export GmbH Friedrich-Ebert-Strasse

54-40210 Dusseldorf, Germany

Classification of Product : Acrylic Coating
General Use : Coating for Plastics
Date prepared : 22/June/2015

2 Hazards identification

Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flam. Aerosol Cathegory 1

Acute Toxity Cathegory 4

Skin Irritation, Cathegory 2

Eye Damage, Cathegory 1

Acute Toxity Cathegory 1

H315: Causes skin irritation

H318: Causes serious eye damage

Acute Toxity Cathegory 4

H332: Harmful if inhaled

Specific target organ toxicity - single exposure, Cathegory 3 H335: May cause respiratory irritation
Specific target organ toxicity - single exposure, Cathegory 3 H336: May cause drowsiness or dizziness

Classification (67/548EEC, 1999/45/EC)

Highly Flammable R12: Extremely flammable

Harmful R20/22: Harmful by inhalation and if swallowed Irritant R37/38: Irritating to respiratory system and skin

Irritant R41: Risk of serious damage to eyes

R66: Repeated exposure may cause skin dryness or cracking R67: Vapours may cause drowsiness and dizziness

Labelling elements

Labelling (Regulation (EC) No 1272/2008)

Hazardous pictograms



Signal word Danger

Hazard Statements H222: Extremely flammable aerosol

H229: Pressurized container: may burst if heated

H302: Harmful if swallowed H315: Causes skin irritation H318: Causes serious eye damage H332: Harmful if inhaled H335: May cause respiratory irritation H336: May cause drowsiness or dizziness

EUH066: Repeated exposure may cause skin dryness or cracking

Precautionary statements Prevention

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection

Reaction:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do. continue rinsing.

Hazardous components which must be listed on the label:

CAS 108-10-1 4-Methylpentan-2-one

CAS 71-36-3 Butan-1-

Other hazards ---

Further information ---

3 Composition/Information on Ingredients

Mixtures

Mixture of solvents in aerosol can

Chemical Name	CAS-No.	EC No.	Registration		Classification (REGULA-	Conc.(wt%)
			Number	(67/548/EEC)	TION (EC) No. 1272/2008	
4-Methylpentan-2-one	108-10-1	203-550-1	01-	F; R11	Flam. Liq. 2; H225	10-20
			2119473980-	Xn; R20	Eye Irrit. 2; H319	
			30-XXXX	Xi; R36/37	Acute Tox. 4; H332	
				R66	STOT SE 3; H335	
1-Methoxy-2-propanol	107-98-2	203-539-1	01-	R10	Flam. Liq. 3; H226	1-5
			2119457435-	R67	STOT SE 3; H336	
			35-XXXX			
n-Butyl-actetate	123-86-4	204-658-1	01-	R10	Flam. Liq. 3; H226	1-5
			2119485493-	R67	STOT SE 3; H336	
			29-XXXX	R66		
Ethanol	64-17-5	200-578-6	01-	F; R11	Flam. Liq. 2; H225	<1
			2119457610-			
			43-XXXX			
Butanone	78-93-3	201-159-0	01-	F; R11	Flam. Liq. 2; H225	5-10
			2119457290-	Xi; R36	Eye Irrit. 2; H319	
			43-XXXX	R67	STOT SE 3; H336	
				R66		
Butan-1-ol	71-36-3	200-751-6	01-	R10	Flam. Liq. 3; H226	1-5
			2119484630-	Xn; R22	Acute Tox. 4; H302	
			38-XXXX	Xi; R37/38	Skin Irrit. 2; H315	
				R41	Eye Dam. 1; H318	
				R67	STOT SE 3; H335	
					STOT SE 3: H336	
2-Butoxyethanol	111-76-2	203-905-0	01-	Xn;	Acute Tox. 4; H312	<1
			2119475108-	R20/21/22	Acute Tox. 4; H332	
			36-XXXX	Xi; R36/38	Acute Tox. 4; H302	
					Skin Irrit. 2; H315	
					Eye Irrit. 2; H319	
Dimethyl ether	115-10-6	204-065-8	01-	F+; R12	Press.Gas	60-70
-			2119472128-		Flam. Gas 1; H220	
			37-XXXX			

For the full text of the R-phrases mentioned in this section, see section 16. For the full text of the H-statements mentioned in this section, see section 16.

4 First-Aid measures

[If in Eyes]

• Wash eyes with plenty of water and in case of persistence of irritation, get medical attention.

[If on Skin]

• Wash with plenty of soap and water, and get medical attention immediately.

[If Inhaled]

- If feel unwell because of inhalation, remove to fresh air and keep at rest in a position comfortable for breathing, and call a physician. [If Swallowed]
- Call a physician immediately.

5 Fire-Fighting measures

Suitable extinguishing media Water[] CO2[*] Foam[*] Dry chemical[*] Dry sand[*]

Fire fighting method

- · Wear proper protective clothes such as heat insulating clothes/gloves/face shield and/or eye protection.
- · Use specified extinguishing media.
- · Remove combustible material from surrounding area.
- · Start fire fighting from windward
- · Do not use water as the extinguishing media.

6 Accidental release measures

- · Avoid contact with skin. Wear appropriate protective equipment (protective gloves, eye/face protection, apron and long sleeved clothes) when handling spill of this product.
- Dispose contaminant and waste in accordance with regulations relative to disposal.
- Eliminate all ignition sources such as heat, sparks, open flames and combustible materials.
- Provide appropriate extinguisher to prepare for fire.
- Do not use steel tools as it may cause impact sparks. Tool should be static free.
- · Absorb with dry sand, earth or noncombustible material. In case of large spill, hold back with earth to prevent spreading.
- · Avoid release to rivers to prevent effect to environment.

7 Handling and storage

[Cautions on Handling]

- · May cause poisoning if on skin or inhaled.
- · Keep away from ignition sources such as heat/sparks/open flame, and ventilate work area when handling this product.
- · Ventilate work area to prevent inhalation of vapor/fume/spray/dust.
- · Avoid contact with skin. Wear protective gloves,eye/face protection and long sleeved clothes if necessary.
- If spilled or leaked, wipe with cloth and discard contaminated materials into a container which is filled with water.
- · Dip contaminated cloth, spray dust and/or mist into water until they are discarded properly.
- · After use, wash hands and gargle mouth thoroughly.
- Do not use this product other than the purpose specified by the manufacturer/supplier.

[Cautions on Storage]

- · Keep container tightly closed. Store in cool and ventilated indoor place. Protect from direct sun light.
- · Keep reach out of children.
- · Keep away from flame or heat sources.

8 Exposure Controls/Personal Protection

[Facilities Recommendation]

- · All facilities should be explosion proof.
- Prevent vapor from retention by installation of a proper ventilator.
- Ground/bond container or receiving equipment for transportation, mixing and/or transferring of this product.
- Do not locate heat/flame generating facilities close to the work area.
- · If spray indoor, install coating facilities so that workers are protected from direct exposure to spray mist, or install adequate ventilation.
- For handling in closed tanks, install appropriate ventilator which secures ventilation to the bottom of the tank.

[Protective Equipments]

- Respiratory Protection: Wear gas mask for organic gas. Wear self-contained breathing apparatus in case of operation in closed areas.
- Eye Protection: Wear goggle type of eye protection.
- Skin Protection: Wear appropriate gloves which is impervious to organic solvents and chemicals.
- Other Protection: Work clothes specified by the manufacturer or supplier, and safety shoes.

		Exposure Limit Value				
		Short Term		Eig	ht Hours	
			AGS&DFG		AGS&DFG	
Substance	CAS No.	EU	Germany	EU	Germany	
Titanium Oxide (TiO2)	13463-67-7	0,3	0,3mg/m³		10mg/m³	
Silicium dioxide	14808-60-7	no data available		0,1mg/m³		
4-Methylpentan-2-one	108-10-1	50ppm/200mg/m ³		20ppm		
n-Butyl acetate	123-86-4	100ppm/475mg/m ³		150ppm		
2-Propanol, 1-methoxy-	107-98-2	no data available		5	0ppm	
Ethanol	64-17-5	no data available		1000ppm		
Butan-2-one	78-93-3	200ppm/590mg/m ³		200ppm		
Butan-1-ol	71-36-3	max50ppm/max150mg/m³		20ppm		
2-Butoxyethanol	111-76-2	25ppm 20ppm		:0ppm		
Dimethyl ether	115-10-6	no data available no data avail		a available		

9 Physical and Chemical Properties

Physical appearance

Colour WHITE Aerosol/liquid Form Order Solvent odor

Additional data

Change of state Pressure of gas is immediately ejected gas.

Sprayed solvents evaporate quickly.

Boiling point/range -23.6°C Flash point -35,2°C

Spray and evaporative gases are extremely flammable. 270°C Flammability

Ignition point Auto Iginition

the case of overheating Oxidizing properties

Explosion Danger overheating rupture/bursting of the container Formation of exposive mixtures are possible.

Explosion limits 1,2 - 26,7 vol%

at 50°C maximum 2/3 of maximum pressure Vapour pressure inside the dispenser

allowed for the dispenser 0.900±0.100g/cm3

Density, here: apparent density at 20°C

Solubility in water

yes
* The finished preparation in the aerosol dispenser More details

only upon the addition of the pressurized gas. * Details are in the hermetically sealed under pressure not measurable container.

10 Stability and Reactivity

[Reactivity Information]

· Materials to be avoided: Keep away from strong oxides and/or peroxides that will cause polymerization and/or generate heat or fire by mixing or

- · Hazardous thermal decomposition products: CO, CO2, HCl, vapors of solvents.
- · Other reactivity information: None.

11 Toxicological Information

Health Hazard Information on Ingredient Table 1

Substance name		Acute toxicity (LD50, LC50, etc.)				
Substance name		Oral	Dermal	Inhalation (Gas)	Inhalation (Vapor)	Inhalation (Dust, Mist)
Titanium oxide (TiO2)	No	ot Categorized	Not Categorized	Not Applicable	Not Classifiable	Not Categorized
Titaliidiii oxide (1102)						
Silicon dioxide	No	ot Categorized	Not Classifiable	Not Applicable	Not Classifiable	Not Classifiable
Silicon dioxide	3	3160mg/kg				
2-Pentanone, 4-methyl-	No	ot Categorized	Not Categorized	Not Applicable	Category 3	Not Classifiable
2 i chanone, 4 metryi	2	2080mg/kg	16000mg/kg		2000ppm	
Acetic acid, butyl ester	No	ot Categorized	Not Categorized	Not Applicable	Category 3	Category 4
Acetic acia, batyl estel	1.	4130mg/kg			2000ppm	0,74mg/l
2-Propanol, 1-methoxy	No	ot Categorized	Not Categorized	Not Applicable	Category 4	Not Classifiable
2-i Topanoi, 1-inethoxy	5	5200mg/kg	13000mg/kg		7395ppm	
Ethanol	No	ot Categorized	Not Classifiable	Not Applicable	Not Categorized	Not Classifiable
Litation	>	5000mg/kg	>20000mg/kg		20661ppm	
2-Butanone	No	ot Categorized	Not Categorized	Not Applicable	Category 4	Not Classifiable
2-Butarione	2	2483mg/kg	>5000mg/kg		11700ppm	
1-Butanol	(Category 4	Not Categorized	Not Applicable	Not Categorized	Not Classifiable
1-Butanoi	1	1227mg/kg	3636mg/kg			
2-Butoxyethanol	(Category 2	Category 3	Not Applicable	Category 2	Not Classifiable
2-Dutoxyeti iarioi		470mg/kg	300mg/kg		450ppm	
Methane, oxybis-	No	lot Classifiable	Not Classifiable	Not Categorized	Not Applicable	Not Applicable
ivieti ane, oxybis-		_		164000ppm		

Health Hazard Information on Ingredient Table 2

Substance name	Skin Corrosion, Irritation	Serious Damage to Eyes /Eye Irritation	Respiratory Sensitization	Skin Sensitization	Germ Cell Mutagenicity	Carcinogenicity
Titanium oxide (TiO2)	Not Categorized	Category 2B	Not Classifiable	Not Classifiable	Not Categorized	Category 2
Silicon dioxide	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Categorized
2-Pentanone, 4-methyl-	Not Categorized	Category 2B	Not Classifiable	Not Categorized	Not Categorized	Category 2
Acetic acid, butyl ester	Not Categorized	Category 2B	Not Classifiable	Not Categorized	Not Classifiable	Not Classifiable
2-Propanol, 1-methoxy	Not Categorized	Category 2B	Not Classifiable	Not Classifiable	Not Categorized	Not Categorized
Ethanol	Not Categorized	Category 2B	Not Classifiable	Not Classifiable	Category 1B	Not Classifiable
2-Butanone	Category 2	Category 2B	Not Classifiable	Not Classifiable	Not Categorized	Not Categorized
1-Butanol	Category 2	Category 2A	Not Classifiable	Not Classifiable	Not Categorized	Not Categorized
2-Butoxyethanol	Category 2	Category 2A	Not Classifiable	Not Categorized	Not Categorized	Not Categorized
Methane, oxybis-	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable	Not Classifiable

Health Hazard Information on Ingredient Table 3

Substance name	Reproductive toxicity	Specific Target Organ (Single Exposure)
Titanium oxide (TiO2)	Not Classifiable	Not Classifiable
Silicon dioxide	Not Classifiable	Not Classifiable
2-Pentanone, 4-methyl-	Not Categorized	Category 3(Respiratory tract irritation, Narcotic effects)
Acetic acid, butyl ester	Not Categorized	Category 2 (Organ of respiratiom, Central nervous system)
2-Propanol, 1-methoxy	Not Categorized	
Ethanol	Category 1A	Category 3(Respiratory tract irritation, Narcotic effects)
2-Butanone	Not Categorized	
1-Butanol	Not Categorized	Category 3(Respiratory tract irritation, Narcotic effects)
2-Butoxyethanol	Category 2	Category 1 (Central nervous system, Blood, Kidney, Liver))
Methane, oxybis-	Not Classifiable	Category 3 (Narcotic effects)

Health Hazard Information of Ingredient Table 4

Substance name	Specific Target Organ (Repeat Exposure)	Aspiration Respiratory Toxicity
Titanium oxide (TiO2)	Not Classifiable	Not Classifiable
Silicon dioxide	Not Classifiable	Not Classifiable
2-Pentanone, 4-methyl-	Not Categorized	Not Categorized
Acetic acid, butyl ester	Category 3	Not Categorized
2-Propanol, 1-methoxy	Not Categorized	Not Categorized
Ethanol	Not Categorized	Not Categorized
2-Butanone	Not Categorized	Not Categorized
1-Butanol	Not Categorized	Not Categorized
2-Butoxyethanol	Not Categorized	Not Categorized
Methane, oxybis-	Not Categorized	Not Categorized

12 Ecological information

Aqueous Milieu Hazard Information on Ingredient

Aqueous Milleu Hazaru Information on Ingredient		
Substance name	Hazardous to Aquatic Environment (Acute)	Hazardous to Aquatic Environment (Chronic)
Titanium oxide (TiO2)	Not Classificable	Not Classificable
Silicon dioxide	Not Classificable	Not Classificable
2-Pentanone, 4-methyl-	Not Categorized	Not Categorized
Acetic acid, butyl ester	Category 3	Not Categorized
2-Propanol, 1-methoxy-	Not Categorized	Not Categorized
Ethanol	Not Categorized	Not Categorized
2-Butanone	Not Categorized	Not Categorized
1-Butanol	Not Categorized	Not Categorized
	Not Categorized	Not Categorized
Methane, oxybis-	Not Categorized	Not Categorized

13 Disposal Considerations

- Content should be used up before disposal of container.
- Container/content should be disposed in accordance with local, regional and national regulations.

14 Transport Information

General Information: Follow general instructions described in the "Precautions on Handling and Storage".

Ground Transportation: Transportation must be done in accordance with the appropriate regulations in case this product falls under a

category of regulations such as Fire Service Law (Japan), Industrial Safety and Health Law (Japan), etc.

Marine Transportation: Comply stipulation of appropriate maritime regulations.

Air Transportation: Comply stipulations of appropriate air transportation regulations.

UN Number: 1950

15 Regulatory Information

Particlar hazards associated with the preparation and safety recommendations:

16 Other Information

Full text risk of R-phrases referred to under sections 2 and 3:

R10: Flammable

R11: Highly flammable R12: Extremely flammable R20: Harmful by inhalation

R20/22: Harmful by inhalation and if swallowed

R22: Harmful if swallowed R36: Irritating to eyes

R36/37: Irritating to eyes and respiratory system R37/38: Irritating to respiratory system and skin

R41: Risk of serious damage to eyes

R66: Repeated exposure may cause skin dryness or cracking

R67: Vapours may cause drowsiness and dizziness

Full text risk of H-statemens referred to under sections 2 and 3:

H220: Extremely flammable gas

H222: Extremely flammable aerosol

H225: Highly flammable liquid and vapour

H226: Flammable liquid and vapour

H229: Pressurized container: may burst if heated

H302: Harmful if swallowed

H315: Causes skin irritation

H318: Causes serious eye damage

H319: Causes serious eye irritation

H332: Harmful if inhaled

H335: May cause respiratory irritation

H336: May cause drowsiness or dizziness

EUH066: Repeated exposure may cause skin dryness or cracking

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Parts of the Safety Data Sheet marked with red line are actualalized.